



NOTES:

1. LEAK TEST: 800 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. REF-OPERATING TEMPERATURE -20°C TO 150°C.
7. DIMENSIONS ARE INCHES [millimeters].

14	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
13	1	-914 VITON	O-RING -914 VITON 75
12	4	EE22 UL1180 YLW	WIRE 22EE UL1180 7/#30
11	4	EE22 UL1180 WHT	WIRE 22EE UL1180 7/#30
10	4	EE22 UL1180 VIO	WIRE 22EE UL1180 7/#30
9	4	EE22 UL1180 RED	WIRE 22EE UL1180 7/#30
8	4	EE22 UL1180 GRY	WIRE 22EE UL1180 7/#30
7	4	EE22 UL WHT/YEL	WIRE 22EE UL1180 7/#30
6	4	EE22 UL WHT/ORG	WIRE 22EE UL1180 7/#30
5	4	EE22 UL WHT/GRN	WIRE 22EE UL1180 7/#30
4	4	EE22 UL WHT/BLU	WIRE 22EE UL1180 7/#30
3	4	EE22 UL WHT/BLK	WIRE 22EE UL1180 7/#30
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	3689	HOUSING SO19-PS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SO19-PS-200-40-TEE22-96-96

PART NUMBER
3673

MATERIAL NOTED
 REVISION LEVEL A
 PROJECTION