



PAVE#	"X"	"Y"
3690	12 [305]	.36
3690-1	36 [914]	.96

NOTES:

1. LEAK TEST: 300 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING WITH MATING CONNECTOR.
3. CONTINUITY TEST: < "Y" mΩ WIRE ENDS TO MATING CONNECTOR
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. ITEM 8 IS INCLUDED BUT NOT SHOWN.
7. REF-OPERATING TEMPERATURE -20°C TO 125°C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION
8	1	SCP06DM24-9S	PLUG 2 #4 SOCKET 5015 SERIES
7	1	0199	NUT VS22-SS (316SS)
6	4	6-32X.375 SS	SCREW 6-32 X .375 STAINLESS STEEL SOCKET HEAD CAP SCREW
5	1	-224 VITON	O-RING -224 VITON 75
4	2	EE4 BLACK	WIRE 4EE 133/#25 WRAPPED
3	1	SCP02ZM24-9P	RCPT 2 #4 PIN 5015 SERIES
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3705	HOUSING VS22-SS W/ 4X6-32UN

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION
VS22-SS-150-2-TEE4-3102P-X

PART NUMBER: **3690***

MATERIAL: NOTED

REVISION LEVEL: A

PROJECTION:

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS