



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 8 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN  $\phi 0.035$  [.89] ARE NOT ACCEPTABLE.
7. WIRE ENDS ARE LABELED WITH CORRESPONDING NUMBERS.
8. REF-OPERATING TEMPERATURE -20 °C TO 200 °C.
9. DIMENSIONS ARE INCHES [millimeters].

4	16	-	BRADY WIRE MARKERS (1-8)
3	8	KT24	CABLE T/C TYPE K 24AWG TEFLON
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	3297	HOUSING PT12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PT12-SS-200-8P-KT24-72-120

PART NUMBER	MATERIAL	NOTED
3691		
REVISION LEVEL	-	PROJECTION
		

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS