



NOTES:

1. HE LEAK TEST @ 1ATM 10x10⁻⁹ CC/S OR LESS.
2. HYPOT 100 VDC 50 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE, SHIELD AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
6. VOIDS SMALLER THAN ϕ .035 [.89] ARE ACCEPTABLE.
7. DIMENSIONS ARE INCHES [millimeters].
8. REF-OPERATING TEMPERATURE RANGE -20°C TO 105°C.

5	1	1014	NUT VS18-SS
4	1	-219 VITON	O-RING -219 VITON 75
3	8	RPS20	CABLE T/C #20 TYPE RS POLYVINYL TWISTED SHIELDED
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0660	HOUSING VS18-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION VS18-SS-150-8TWSH-RPS20-300-60	
PART NUMBER 3692	MATERIAL NOTED
REVISION LEVEL -	PROJECTION ☉

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS