


NOTES:



1. LEAK TEST: 1500 PSI, NO BUBBLES 30 SECONDS MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. ATTENUATION <.5dB @ 1300nm CONNECTOR TO CONNECTOR.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø0.035 [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
7. REF-OPERATING TEMPERATURE -40 °C TO 125 °C.
8. REF-PARTS ARE DEFLASHED ON PARTING LINE +0.005 [.13] MAXIMUM.
9. DIMENSIONS ARE INCHES [millimeters].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

8	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
7	2	-012 VITON LT	O-RING -012 LOW-TEMP VITON V835-75
6	1	1060242030	CONNECTOR LC FIBER OPTIC 127 UM 2.0CBL
5	1	M85045-16-01	CABLE FIBER MULTIMODE 62.5/125 .078 DIA
4	1	CSPC126NN	FERRULE 2.5mm CERAMIC 126 MICRON
3	1	AMP 502750-1	ADAPTER FO ST CERAMIC
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1226M	HOUSING SP8M-E
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SP8M-E-150-1-STFO-13LC

PART NUMBER
3740

MATERIAL NOTED
 REVISION LEVEL D
 PROJECTION  

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS