



NOTES:

1. LEAK TEST: 150 PSI NITROGEN, NO BUBBLES 45 MINUTES MINIMUM.
2. OPTICAL CONTINUITY CHECK WITH RED LASER, BOTH FIBERS MUST BE GOOD.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS LARGER THAN $\phi 0.035$ [.89] ARE NOT ACCEPTABLE.
6. REF-OPERATING TEMPERATURE RANGE -20°C TO 85°C .
7. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

4	1	-116 VITON	O-RING -116 VITON 75
3	1	3798	FIBER OPTIC 50/125 MULTIMODE DUPLEX ZIPCORD WITH OFNR ORANGE JACKET INCLUDING 2 LC CONNECTORS & 1 LC CLIP EACH END 44 METER LENGTH
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1180	HOUSING VS12L-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION VS12L-SS-150-1-DUPLEXFO-40mLC-4mLC	
PART NUMBER 3767	MATERIAL NOTED
REVISION LEVEL -	PROJECTION ☉

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS