


NOTES:

1. HE LEAK TEST VACUUM 10×10^{-8} CC/SEC OR LESS.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. VOIDS LARGER THAN $\phi 0.035$ [.89] ARE NOT ACCEPTABLE.
5. REF-OPERATING TEMPERATURE RANGE -20°C TO 125°C .
6. PART IS SHIPPED WITH CONNECTORS UNFURLED AND ITEM 5 IN THE APPROXIMATE LOCATION SHOWN TO PROTECT SURFACE FINISH ON ITEM 1.
7. DIMENSIONS ARE INCHES [millimeters].


5	2	7524T15	FILM CLEAR PVC STATIC CLING .007"
4	4	2-56X.188BHCSSS	SCREW BUTTON SHCS 2-56X.188 SS
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	2	05-0028-01	ASSEMBLY HEADER 12 PIN FLEX
1	1	10-0367-04	PLATE TOP ALUMINUM
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SQF50-AL-150-24-24-PIN-PIN

PART NUMBER
3870

MATERIAL NOTED

REVISION LEVEL -
 PROJECTION 

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS