



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PINS TO PINS.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø0.035 ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. REF-OPERATING TEMPERATURE -20°C TO 105°C.
7. DIMENSIONS ARE INCHES [millimeters].
8. PAVE-Seal CAN BE BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	1	-030 VITON	O-RING -030 VITON 75
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	163A16819X	CONNECTOR DSUB 44HDPIN MALE
ITEM	QTY.	PART #	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
SP40/13-E-150-44-20-DSUB-PIN

PART NUMBER
4263

MATERIAL NOTED

REVISION LEVEL
D

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS