



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-7} CC/SEC OR LESS.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. CABLE POSITIONING IS APPROXIMATE & VARIABLE.
5. VOIDS SMALLER THAN $\phi 0.035$ [.89] ARE ACCEPTABLE.
6. REF-OPERATING TEMPERATURE -20°C TO 105°C .
7. PAVE-SEAL CAN BE A BIDIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
8. DIMENSIONS ARE INCHES [millimeters].

5	1	0199	NUT VS22-SS
4	1	-224 VITON	O-RING -224 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	3	2517	CABLE RIBBON 20/# 28 14.50"
1	1	0189/304SS	HOUSING VS22-SS
ITEM	QTY	PART #	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
VS22-SS-150-3-20RIB-6-6

PART NUMBER
4327

MATERIAL
NOTED

REVISION LEVEL
-

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS