



**NOTES:**

1. LEAK TEST 80 PSI, NO BUBBLES 6 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEG OHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS SMALLER THAN  $\phi 0.035$  [.89] ARE ACCEPTABLE.
7. RE-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

|      |     |               |                                  |
|------|-----|---------------|----------------------------------|
| 3    | 6   | TI20          | CABLE T/C TYPE T# 20 TEFLO N FEP |
| 2    | A/R | PAVE-Seal 150 | EPOXY BLACK                      |
| 1    | 1   | 4206          | HOUSING PT12-B                   |
| ITEM | QTY | PART#         | DESCRIPTION                      |

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

|   |                   |
|---|-------------------|
| DESCRIPTION<br>PT12-B-150-6P-TI20-72-72 |                   |
| PART NUMBER<br><b>4363</b>              | MATERIAL<br>NOTED |
| REVISION LEVEL<br>-                     | PROJECTION<br>☉ ◻ |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS