



NOTES:

1. LEAK TEST: 10,000 PSI, NO BUBBLES 30 SECONDS MINIMUM.
CUSTOMER QUALIFICATION TEST: 15,000 PSI N2, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM SPLICE TO SPLICE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. NO COSMETIC SURFACE VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, COSMETIC SURFACE VOIDS SMALLER THAN Ø0.035 [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
7. REF-OPERATING TEMPERATURE -20 °C TO 150 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	1	B/U RING -008	BACK UP RING -008 SINGLE TURN
3	1	-008 VITON	O-RING -008 VITON 75
2	2	4461	SPLICE BUTT #22D HIGH-PRESSURE
1	A/R	PAVE-Seal 200	EPOXY BLACK
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
SP5X-E-200-2-26-SC-SC

PART NUMBER
4460

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS