



INSTALL USING #6-32 SCREWS & #6 (.375 O.D.) WASHERS, NOT SUPPLIED

NOTES:

1. HE LEAK TEST @ 1 ATM 10X10⁻⁸ CC/SEC OR LESS. LEAK TEST PERFORMED WITH A 2-030 VITON O-RING, NOT INCLUDED.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. NO COSMETIC SURFACE VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
5. PAVE PART NUMBER 4469-BLANK DOES NOT INCLUDE ITEM 2, NO FLEX CABLE.
6. DIMENSIONS ARE INCHES [millimeters].
7. REF-OPERATING TEMPERATURE -40 °C TO 85 °C.
8. REF-PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAXIMUM.

| ITEM | QTY | PART NUMBER | DESCRIPTION |
|------|-----|---------------|-----------------------------|
| 2 | 1 | 4469FLEX | CABLE FLEX KAPTON INSULATED |
| 1 | A/R | PAVE-Seal 150 | EPOXY BLACK |

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

| | |
|--|---------------------------------------|
| DESCRIPTION SP41.2/6.4-E-150-1-FLEX-8-6 | |
| PART NUMBER 4469 | MATERIAL NOTED REVISION LEVEL A |
| PROJECTION ⊙ ◁ | |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS