



NOTES:

1. LEAK TEST: 3000 PSI, NO BUBBLES 2 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. OPTICAL CONTINUITY CHECK WITH RED LASER.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. COSMETIC SURFACE VOIDS LARGER THAN $\phi 0.035$ [0.89] ARE NOT ACCEPTABLE.
6. REF-OPERATING TEMPERATURE -20°C TO 125°C .
7. DIMENSIONS ARE INCHES [millimeters].
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	1	-905 VITON	O-RING -905 VITON 75
3	1	14T73-0007-002	CABLE MMFO 200/220um SMA905 QUARTZ/ POLYIMIDE/HYTREL WITH FLEXIBLE 304SS TUBE
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4491	HOUSING SO8M-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SO8M-SS-150-1-200/220umMMFO-589-04

PART NUMBER

4485

MATERIAL NOTED

REVISION LEVEL D

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS