



- NOTES:
1. HE LEAK TEST @ 1 ATM. 1×10^{-7} CC/SEC OR LESS.
 2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 3. ALL PARTS MUST PASS ALL TESTS.
 4. NO COSMETIC SURFACE VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
 5. REF-OPERATING TEMPERATURE -20°C TO 125°C .
 6. MAXIMUM TEMPERATURE ALLOWED: 125°C .
 7. DIMENSIONS ARE INCHES [millimeters].
 8. USING A LAMINAR FLOW HOOD, PARTS ARE CLEANED OF CONTAMINANTS WITH ISOPROPYL ALCOHOL AND SEALED IN INDIVIDUAL BAGS.

ITEM	QTY	PART NUMBER	DESCRIPTION
2	1	U9320-68143	FLEX CABLE
1	A/R	PAVE-Seal 150	EPOXY BLACK

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
SP26.4/7.2-E-150-1-FLEX

PART NUMBER
4880

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS