



NOTES:

1. LEAK TEST: 5000 PSI, NO N2 BUBBLES 5 SECONDS MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
7. COSMETIC SURFACE VOIDS SMALLER THAN ϕ 0.035 [0.89] ARE ACCEPTABLE.
8. REF-OPERATING TEMPERATURE RANGE -20 °C TO 150 °C.
9. DIMENSIONS ARE INCHES [millimeters].

7	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
6	1	-905 VITON	O-RING -905 VITON 75
5	1	E26 WHITE	WIRE 26E MIL-W-16878/4 7/#34
4	1	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
3	1	E26 GREEN	WIRE 26E MIL-W-16878/4 7/#34
2	A/R	PAVE-Seal 200	EPOXY BLACK HIGH TEMP
1	1	4838	HOUSING SO8S-SS HEX PRESSURE
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SO8S-SS-200-3-TE26-6-6

PART NUMBER
4896

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE \pm 0.5
 X.X DECIMAL \pm 0.1 X.XX DECIMAL \pm 0.02 X.XXX DECIMAL \pm 0.005
 ANGLES \pm 1 DEGREE SURFACE FINISH 128 microinch RMS