



**NOTES:**

1. LEAK TEST: 2500 PSI, NO BUBBLES 1 MINUTE MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 1000 VDC 100 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. OPTICAL CONTINUITY CHECK, 2 MINIMUM GOOD FIBERS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRES & FIBERS ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
7. WIRE & FIBER POSITIONING IS APPROXIMATE & VARIABLE.
8. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
9. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
10. REF-OPERATING TEMPERATURE RANGE -20 °C TO 120 °C.
11. REF-PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAXIMUM.
12. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
13. DIMENSIONS ARE INCHES [millimeters].

10	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
9	2	-015 N0674-70	O-RING -015 NBR 70
8	3	NFO(EP)-125-4B	FIBER OPTIC SINGLEMODE BEND-INSENSITIVE 900um BUFFERED
7	1	55A0421-26-9/92	WIRE TZ26 19/#38 TPC TWST PR WHT & WHT/RED STRIPE
6	1	55A0421-26-9/93	WIRE TZ26 19/#38 TPC TWST PR WHT & WHT/ORANGE STRIPE
5	1	55A0421-26-9/95	WIRE TZ26 19/#38 TPC TWST PR WHT & WHT/GREEN STRIPE
4	1	55A0421-26-9/96	WIRE TZ26 19/#38 TPC TWST PR WHT & WHT/BLUE STRIPE
3	1	FRCL-122111	CABLE CAT 6 UNJACKETED NO SHIELD (ONLY 2 TWISTED PAIRS OF 4 USED, BLU/WHT W/BLU STRIPE & ORG/WHT W/ORG STRIPE)
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1374 M	HOUSING SP11M-E
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 SP11M-E-150-2TPT/4TP/2-CAT6/TZ26/SMFO-190-12

PART NUMBER  
**5033**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS