



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 7 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN $\phi .035$ [0.89] ARE ACCEPTABLE.
7. WIRE ARE MARKED ON BOTH ENDS WITH A UNIQUE NUMBER.
8. REF-OPERATING TEMPERATURE RANGE -40°C TO 150°C .
9. DIMENSIONS ARE INCHES [millimeters].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION
4	16	-	BRADY WIRE MARKERS (NUMBERS 1-8)
3	8	KT24	CABLE T/C TYPE K 24AWG TEFLON
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0346-1	HOUSING PT-8 SS

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION
PT8-SS-200-8P-KT24-120-40

PART NUMBER
5052

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE. SURFACE FINISH 128 microinch RMS