


NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES, 2 MINUTES MIN. A GREEN PAINT DOT INDICATES PART HAS PASSED THIS TEST
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN  $\phi .035$  [.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

| 6    | 1   | EE10 RED      | WIRE 10EE MIL-W-16878/5 .017 37/#26 |
|------|-----|---------------|-------------------------------------|
| 5    | 1   | EE10 GREEN    | WIRE 10EE MIL-W-16878/5 .017 37/#26 |
| 4    | 1   | EE10 BLUE     | WIRE 10EE MIL-W-16878/5 .017 37/#26 |
| 3    | 1   | EE10 BLACK    | WIRE 10EE MIL-W-16878/5 .017 37/#26 |
| 2    | A/R | PAVE-Seal 150 | EPOXY BLACK                         |
| 1    | 1   | 1132          | HOUSING PTN16-SS                    |
| ITEM | QTY | PART NUMBER   | DESCRIPTION                         |


 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PTN16-SS-150-4-TEE10-24-24

PART NUMBER  
**1786**

MATERIAL NOTED  
 REVISION LEVEL A  
 PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS