



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST. TEST IS PERFORMED USING A MISUMI# GS-C-EPDM-2.0S GASKET, MATING CLF3(2.0) FERRULE, & MISUMI# SNCPH2S MEDIUM/HIGH PRESSURE FERRULE CLAMP.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. MINIMUM OF 15 GOOD WIRES (ITEM 3) REQUIRED.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
8. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
9. REF-OPERATING TEMPERATURE -55°C TO 120°C .
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	16*	JT28	*SEE NOTE 3	CABLE T/C TYPE J 28AWG TEFLON
2	A/R	PAVE-Seal 200		EPOXY BLACK
1	1	5072		HOUSING CLF3(2.0)-316LSS
ITEM	QTY	PART NUMBER		DESCRIPTION


 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 CLF3(2.0)-316LSS-200-15P-JT28-10M-10M

PART NUMBER	MATERIAL	NOTED
5068		
REVISION LEVEL	-	PROJECTION
		

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS