



NOTES:

1. HE LEAK TEST @ 1 ATM. 1X10⁻⁸ CC/SEC OR LESS. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 1000 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING WITH MATING CONNECTORS.
3. CONTINUITY TEST < 0.5 Ohm PIN TO SOCKET WITH MATING CONNECTORS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. ALCOHOL OR FOMBLIN YVAC 3 MAY BE USED TO LUBRICATE O-RINGS FOR VACUUM HELIUM LEAK TESTING.
7. ADDING "NP" TO THE PAVE PART NUMBER AND ORDER CODE INDICATES THAT ITEMS 7 & 8 ARE NOT INCLUDED (NO PLUGS).
8. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:
 <= .5 [12.7] SEAL DIAMETER: Ø .035 [.89] MAX ALLOWED VOID SIZE
 > .5 [12.7] SEAL DIAMETER: Ø .060 [1.5] MAX ALLOWED VOID SIZE
9. REF-OPERATING TEMPERATURE RANGE -20 °C TO 125 °C.
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION
8	1	SCP06PM28-21P	*SEE NOTE 7 PLUG 37#16 PIN NICKEL PLATED ALUMINUM SHELL & S/R BLUE DIALLYL PHTHALATE INSERT SILVER PLATED SOLDER CUP CONTACTS
7	1	SCP06PM28-21S	*SEE NOTE 7 PLUG 37#16 SOC NICKEL PLATED ALUMINUM SHELL & S/R BLUE DIALLYL PHTHALATE INSERT SILVER PLATED SOLDER CUP CONTACTS
6	1	0185	NUT VS26-SS
5	1	-226 VITON	O-RING -226 VITON 75
4	1	SCP02PM28-21S	RCPT 37#16 SOC NICKEL PLATED ALUMINUM SHELL BLUE DIALLYL PHTHALATE INSERT
3	1	SCP02PM28-21P	RCPT 37#16 PIN NICKEL PLATED ALUMINUM SHELL BLUE DIALLYL PHTHALATE INSERT
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4007	HOUSING VS26-SS

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION
VS26-SS-150-37-16-3102PS

PART NUMBER
1583

MATERIAL NOTED

REVISION LEVEL
F

PROJECTION
⊙ ◁

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS