



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MIN. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST. QUALIFICATION TEST: HE LEAK TEST @ 1ATM. 1X10<sup>-7</sup> CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:  
 <= .5 [12.7] SEAL DIAMETER: Ø .035 [.89] MAX ALLOWED VOID SIZE  
 >= .5 [12.7] SEAL DIAMETER: Ø .060 [1.5] MAX ALLOWED VOID SIZE
7. REF-OPERATING TEMPERATURE -20 °C TO 120 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].
10. FINISHED PRODUCT IS REACH AND RoHS COMPLIANT.

ITEM	QTY.	PART #	DESCRIPTION
3	6	TT20	CABLE T/C TYPE T #20 TEFLON FEP
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3545	HOUSING PT8-SS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PT8-SS-150-6P-TT20-18-32

PART NUMBER <b>5066</b>	MATERIAL NOTED	REVISION LEVEL A	PROJECTION ☉ ◻
----------------------------	-------------------	---------------------	-------------------

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS