



NOTES:

1. LEAK TEST: 300 PSI, NO BUBBLES 1 MINUTE MINIMUM PER SEAL, EACH SEAL TESTED INDIVIDUALLY. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND SHIELDS.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. NO COSMETIC SURFACE VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
9. REF-PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAXIMUM.
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

9	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
8	4	-020 VITON	O-RING -020 VITON 75
7	1	FIT-221-3/4	TUBING SHRINK 3/4" IRRADIATED POLYOLEFIN MIL-I-23053/5-109-0
6	3	E20 RED	WIRE 20E MIL-W-16878/4 .010 7/#28
5	3	E20 BLACK	WIRE 20E MIL-W-16878/4 .010 7/#28
4	5	TEF 2/C #26 TSP	CABLE 2/C BLK/WHT 7/34
3	2	RG316	CABLE COAX BELDEN 83284 OR EQUAL
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	2	4834	HOUSING SP16S-E
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SP16S-E-150-2/5/6-RG316/TSP26/TE20-500-220-500mm

PART NUMBER
4870

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS