



NOTES:

1. LEAK TEST: 310 PSI, NO N2 BUBBLES 1 MINUTE MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE TO SHIELDS AND HOUSING.
3. CONTINUITY TEST SHIELDS < 0.5 OHM END TO END.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. COSMETIC SURFACE NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:
 <= .5 [12.7] SEAL DIAMETER: ϕ .035 [.89] MAX ALLOWED VOID SIZE
 > .5 [12.7] SEAL DIAMETER: ϕ .060 [1.5] MAX ALLOWED VOID SIZE
8. REF-OPERATING TEMPERATURE RANGE -20°C TO 190°C.
9. DIMENSIONS ARE INCHES [millimeters].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
11. PART IS RoHS COMPLIANT.

6	2	250-3866-0000	CABLE COAX 50 OHM PTFE DIELECTRIC RED TTFE JACKET TEXCAL ONLY
5	2	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
4	2	E20 ORG	WIRE 20E MIL-W-16878/4 .010 7/#28
3	1	E18 GREEN	WIRE 18E MIL-W-16878/4 7/#26
2	A/R	PAVE-Seal 200FR	EPOXY BLACK FM/UL V-094 APPROVED
1	1	5146	HOUSING PT8XL-SS
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 PT8XL-SS-200UL94-1/2/2/2-TE18/20/28/COAX-75-10

PART NUMBER	MATERIAL	NOTED
5141		
REVISION LEVEL	-	PROJECTION
		

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS