



NOTES:

1. HE LEAK TEST @ 1 ATM. 1X10<sup>-8</sup> CC/SEC OR LESS. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE TO SHIELDING AND HOUSING.
3. CABLES MUST HAVE CONTINUITY END TO END FOR BOTH SHIELD AND CENTER CONDUCTOR.
4. ALCOHOL OR FOMBLIN YVAC 3 MAY BE USED TO LUBRICATE O-RINGS FOR VACUUM HELIUM LEAK TESTING.
5. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
6. ALL PARTS MUST PASS ALL TESTS.
7. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
8. COSMETIC SURFACE VOIDS SMALLER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
9. REF-OPERATING TEMPERATURE -40°C TO 120°C.
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

7	110	BRADY WIRE MARKERS	NUMBERED 1-55
6	2	STRAIN RELIEF	CABLE CLAMP
5	1	4381	NUT VS44-SS
4	1	-233 VITON LT	O-RING -233 LOW-TEMP VITON 75
3	55	PTFE #20 SHIELDED	CABLE 20AWG PTFE SHIELDED & JACKETED
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4379	HOUSING VS44L-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE. SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 VS44L-SS-150-55-1/CSJ-TE20-10-12m

PART NUMBER  
**5166**

MATERIAL NOTED

REVISION LEVEL PRELIM

PROJECTION