



NOTES:

1. HE LEAK TEST VACUUM 1×10^{-8} CC/SEC OR LESS.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. REF-OPERATING TEMPERATURE -20°C TO 204°C .
5. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
6. DIMENSIONS ARE INCHES [millimeters].

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

ITEM	QTY	PART NUMBER	DESCRIPTION
3	1	0185	NUT VS26-SS
2	1	-226 VITON	O-RING -226 VITON 75
1	1	5185	HOUSING VS26-SS SOLID

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
VS26-SS-PLUG

PART NUMBER
2054

MATERIAL NOTED
 REVISION LEVEL C

PROJECTION