



NOTES:

1. LEAK TEST: 1100 PSI NITROGEN, NO BUBBLES 30 SECONDS MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & COLOR POSITIONS ARE VARIABLE, WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:
 $\leq .5$ [12.7] SEAL DIAMETER: $\phi .035$ [.89] MAX ALLOWED VOID SIZE
 $> .5$ [12.7] SEAL DIAMETER: $\phi .060$ [1.5] MAX ALLOWED VOID SIZE
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE RANGE -34°C TO 121°C .
9. REF-PARTS ARE DEFLASHED ON PARTING LINE $+0.005$ [0.13] MAXIMUM.
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

| | | | |
|-------------|------------|--------------------|-----------------------------------------|
| 17 | A/R | PARKER O-LUBE | LUBRICANT O-RING BARIUM-BASED |
| 16 | 2 | -015 NITRILE | O-RING -015 NITRILE 75 |
| 15 | 1 | TZ24 WHT M/16 | WIRE 24AWG TEFLON M22759/16 |
| 14 | 1 | TZ24 VIO M/16 | WIRE 24AWG TEFLON M22759/16 |
| 13 | 1 | TZ24 YLW M/16 | WIRE 24AWG TEFLON M22759/16 |
| 12 | 1 | TZ24 GRY M/16 | WIRE 24AWG TEFLON M22759/16 |
| 11 | 1 | TZ24 BRN M/16 | WIRE 24AWG TEFLON M22759/16 |
| 10 | 1 | TZ24 ORG M/16 | WIRE 24AWG TEFLON M22759/16 |
| 9 | 1 | TZ24 GRN M/16 | WIRE 24AWG TEFLON M22759/16 |
| 8 | 2 | TZ24 RED M/16 | WIRE 24AWG TEFLON M22759/16 |
| 7 | 1 | TZ24 BLU M/16 | WIRE 24AWG TEFLON M22759/16 |
| 6 | 2 | TZ24 BLK M/16 | WIRE 24AWG TEFLON M22759/16 |
| 5 | 1 | TZ18 WHT /16 | WIRE 18 TEFLON MIL-W-22759/16-18 19/#30 |
| 4 | 1 | TZ18 RED /16 | WIRE 18 TEFLON MIL-W-22759/16-18 19/#30 |
| 3 | 1 | TZ18 BLK /16 | WIRE 18 TEFLON MIL-W-22759/16-18 19/#30 |
| 2 | A/R | PAVE-Seal 150 | EPOXY BLACK |
| 1 | 1 | 1374M | HOUSING SP11M-E |
| ITEM | QTY | PART NUMBER | DESCRIPTION |

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION
SP11M-E-150-12/3-TZ24/18-1-1m

PART NUMBER
5995

MATERIAL
NOTED

REVISION LEVEL
-

PROJECTION
☉

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS