



RECOMMENDED RETAINING RING  
TRUARC N5000-56 OR EQUAL

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1.5 MINUTES MINIMUM. A GREEN PAINT DOT ON THE PRESSURE SIDE INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:  
 <= .5 [12.7] SEAL DIAMETER: Ø.035 [.89] MAX ALLOWED VOID SIZE  
 > .5 [12.7] SEAL DIAMETER: Ø.060 [1.5] MAX ALLOWED VOID SIZE
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE RANGE -40°C TO 150°C.
9. REF-PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAX.
10. DIMENSIONS ARE INCHES [millimeters].
11. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

8	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
7	2	-012 VITON LT	O-RING -012 LOW-TEMP VITON 75
6	1	TZ16 YW	WIRE 16 TEFZEL MIL-W-22759/16 19/#29
5	1	TZ16 RD	WIRE 16 TEFZEL MIL-W-22759/16 19/#29
4	1	TZ16 GREEN	WIRE 16 TEFZEL MIL-W-22759/16 19/#29
3	1	TZ16 BK	WIRE 16 TEFZEL MIL-W-22759/16 19/#29
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	1226L	HOUSING SP8L-E
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 SP8L-E-200-4-TZ16-500mm-500mm

PART NUMBER  
**6028**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS