



- NOTES:
1. HE LEAK TEST @ 3,200 PSI, 1X10<sup>-5</sup> CC/SEC OR LESS. ITEM 5 IS INSTALLED AND TORQUED TO 6 ft-lb (72 in-lb) PRIOR TO LEAK TESTING, A GREEN PAINT DOT ON THE ATMOSPHERE SIDE INDICATES THE PART HAS PASSED THE TEST.
  2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM ROD TO HOUSING.
  3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  4. ALL PARTS MUST PASS ALL TESTS.
  5. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:  
 <= .5 [12.7] SEAL DIAMETER:  $\phi$ .035 [.89] MAX ALLOWED VOID SIZE  
 > .5 [12.7] SEAL DIAMETER:  $\phi$ .060 [1.5] MAX ALLOWED VOID SIZE
  6. REF-OPERATING TEMPERATURE RANGE -20 °C TO 125 °C.
  7. DIMENSIONS ARE INCHES [millimeters].
  8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

6	1	1014	NUT VS18-SS
5	1	1/4-20X.5SSSHCS	SOCKET HEAD CAP SCREW SELF SEALING 1/4-20X.5" VITON O-RING
4	1	-219 VITON	O-RING -219 VITON 75
3	1	5346	ROD .50" COPPER 5.31"
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0660	HOUSING VS18-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
VS18-SS-150-1-.5CU-2.4-1

PART NUMBER  
**5314**

MATERIAL NOTED

REVISION LEVEL  
B

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS