



NOTES:

1. HE LEAK TEST @ 1 ATM. 1X10⁻⁶ CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-600 VITON GASKET. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 300 VDC 50 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL CIRCUITS MUST HAVE CONTINUITY, NO OPEN CIRCUITS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20 °C TO 80 °C.
9. DIMENSIONS ARE INCHES [millimeters].

FINISH
ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MILLIMETERS.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE, ±12.700,
X.X DECIMAL ±1.540, X.XX DECIMAL ±0.508, X.XXX DECIMAL ±0.127,
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

ITEM	QTY	PART NUMBER	DESCRIPTION
5	1	GASKET G-600 C	GASKET CF600 COPPER
4	3	EWS-14049-M25	CABLE SERVO MOTOR POWER 6/C SHIELDED 4#12/2#16 (TP) TPE INSULATION, 300V, 80 °C, OVERALL ORANGE TPU JACKET CONNECTORIZED (25 METER OAL)
3	3	EWS-14050-M25	CABLE SERVO MOTOR POWER 6/C SHIELDED 4#10/2#16 (TP) TPE INSULATION, 300V, 80 °C, OVERALL ORANGE TPU JACKET CONNECTORIZED (25 METER OAL)
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4835	HOUSING CF462-SS (304SS)

PAVE technology co.
2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION: PAVE-Seal® Cable Harnesses
CF600-SS-150-12/12/12-TPE10/12/16-289T-854T

MATERIAL: NOTED

PART NUMBER: 4796

REVISION LEVEL: A

PROJECTION: