


NOTES:

1. LEAK TEST @ 1 ATM. 1X10⁻⁶ CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-462 VITON GASKET. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 300 VDC 50 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL CIRCUITS MUST HAVE CONTINUITY, NO OPEN CIRCUITS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20°C TO 80°C.
9. DIMENSIONS ARE INCHES [millimeters].

FINISH

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MILLIMETERS.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE, ±12.700,
 XX DECIMAL ±1.50, XXX DECIMAL ±0.508, XXXX DECIMAL ±0.127,
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

ITEM	QTY	PART NUMBER	DESCRIPTION
4	1	GASKET G-462 C	GASKET CF462 COPPER
3	6	00-179-966	CABLE RESOLVER 6/C SHIELDED 4#12/2#16 (TP), 300V, 80 °C, OVERALL BLACK POLYURETHANE JACKET CONNECTORIZED (25 METER OAL)
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4836	HOUSING CF462-SS (304SS)



DESCRIPTION PAVE-Seal® Cable Harnesses
 CF462-SS-150-24/12-TPE12/16-318T-834T

MATERIAL NOTED

PART NUMBER	REVISION LEVEL
4797	-
	PROJECTION
	☉