



PIN-OUT TABLE

SOC	ITEM#	T/C # / LEAD COLOR
A	4	T/C #1 / RED (-)
B	5	T/C #1 / YELLOW (+)
C	4	T/C #2 / RED (-)
D	5	T/C #2 / YELLOW (+)
E	4	T/C #3 / RED (-)
F	5	T/C #3 / YELLOW (+)
G	4	T/C #4 / RED (-)
H	5	T/C #4 / YELLOW (+)

NOTES:

1. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM SOCKET TO SOCKET AND HOUSING WITH MATING CONNECTOR.
2. CONTINUITY TEST: <2.1 OHMS SOCKET TO WIRE END WITH MATING CONNECTOR.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN Ø060 [1.5] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE RANGE -20°C TO 105°C.
8. DIMENSIONS ARE INCHES [millimeters].

ITEM	QTY	PART NUMBER	DESCRIPTION
6	4	KP20	CABLE T/C TYPE K 20AWG PVC
5	4	M39029/88-488	CONTACT #20 SOCKET CHROMEL
4	4	M39029/88-487	CONTACT #20 SOCKET ALUMEL
3	1	JVS16A1308BN	PLUG 8#20 SOC BRONZE SHELL THERMOPLASTIC INSERT
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	5232	BACKSHELL 38999 SHELL 13 BRASS

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
D38999/26-B-150-4P-KP20-48

PART NUMBER
5192

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS