



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM. A GREEN PAINT DOT ON THE ATMOSPHERE SIDE INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:  
 <= .5 [12.7] SEAL DIAMETER:  $\phi$ .035 [.89] MAX ALLOWED VOID SIZE  
 > .5 [12.7] SEAL DIAMETER:  $\phi$ .060 [1.5] MAX ALLOWED VOID SIZE
7. REF-OPERATING TEMPERATURE RANGE -20°C TO 125°C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

12	1	E28 YELLOW	WIRE 28E MIL-W-16878/4 .010 7/#36
11	1	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
10	1	E28 VIOLET	WIRE 28E MIL-W-16878/4 .010 7/#36
9	1	E28 RED	WIRE 28E MIL-W-16878/4 .010 7/#36
8	1	E28 ORANGE	WIRE 28E MIL-W-16878/4 .010 7/#36
7	1	E28 GREEN	WIRE 28E MIL-W-16878/4 .010 7/#36
6	1	E28 GRAY	WIRE 28E MIL-W-16878/4 .010 7/#36
5	1	E28 BROWN	WIRE 28E MIL-W-16878/4 .010 7/#36
4	1	E28 BLUE	WIRE 28E MIL-W-16878/4 .010 7/#36
3	1	E28 BLACK	WIRE 28E MIL-W-16878/4 .010 7/#36
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	5083	HOUSING PT12-SS
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PT12-SS-150-10-TE28-11-9

PART NUMBER  
**5199**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS