





NOTES:

- HE LEAK TEST @ 1 ATM. 1X10^-7 CC/SEC OR LESS. A GREEN PAINT DOT ON THE ATMOSPHERE SIDE INDICATES THE PART HAS PASSED THE TEST.
- HYPOT 1000 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING WITH MATING CONNECTORS.
- CONTINUITY TEST < 0.5 OHM PIN TO SOCKET AND RECEPTACLE SHELL TO RECEPTACLE SHELL WITH MATING CONNECTORS.
- ALCOHOL OR FOMBLIN YVAC 3 MAY BE USED TO LUBRICATE O-RINGS FOR VACUUM HELIUM LEAK TESTING.
- ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
- ALL PARTS MUST PASS ALL TESTS.
- COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER: <=.5 [12.7] SEAL DIAMETER: \oint .035 [.89] MAX ALLOWED VOID SIZE > .5 [12.7] SEAL DIAMETER: \emptyset .060 [1.5] MAX ALLOWED VOID SIZE
- REF-OPERATING TEMPERATURE RANGE -20 °C TO 125 °C.
- DIMENSIONS ARE INCHES [millimeters].
- PAVE-SEAL CAN BE A BI-DÎRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION	,
1	1	0189/304SS	HOUSING VS22-SS	P.
2	A/R	PAVE-Seal 150	EPOXY BLACK	
3	1	20GE26PN	RCPT 26#20 PIN NICKEL PLATED ALUMINUM SHELL GOLD PLATED COPPER ALLOY CONTACTS SPACE GRADE	F
4	1	20GE26SN	RCPT 26#20 SOCKET NICKEL PLATED ALUMINUM SHELL GOLD PLATED COPPER ALLOY CONTACTS SPACE GRADE	
5	1	-224 VITON	O-RING -224 VITON 75	
6	1	0199	NUT VS22-SS	

2751 Thunderhawk Court Dayton, OH 45414-3445 PAVE technology co. tel (937) 890-1100 fax (937) 8905165 www.pavetechnologyco.com VS22-SS-150-26-20-99920PS (NP)

PART NUMBER 5715 MATERIAL NOTED \bigcirc

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES. ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS