


RECOMMENDED RETAINING RING
SMALLEY WH-75 OR EQUAL



- NOTES:
1. LEAK TEST: 10,000 PSI, NO BUBBLES 30 SECONDS MINIMUM. A GREEN PAINT DOT ON THE PRESSURE SIDE INDICATES THE PART HAS PASSED THE TEST.
 2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ALL PARTS MUST PASS ALL TESTS.
 5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
 6. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
 7. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:
 <= .5 [12.7] SEAL DIAMETER: ϕ .035 [.89] MAX ALLOWED VOID SIZE
 > .5 [12.7] SEAL DIAMETER: ϕ .060 [1.5] MAX ALLOWED VOID SIZE
 8. REF-OPERATING TEMPERATURE RANGE -25 °C TO 150 °C.
 9. DIMENSIONS ARE INCHES [millimeters].
 10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION
6	1	B/U RING -015	RING BACK UP -015 TEFLON SCARF CUT
5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	2	-015 VITON	O-RING -015 VITON 75 BROWN ONLY
3	8	KT28	CABLE T/C TYPE K 28AWG TEFLON
2	16	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
1	A/R	PAVE-Seal 200	EPOXY BLACK

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SP11H-E-200-16/8P-TE28/KT28-24-24

PART NUMBER
5764

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE. SURFACE FINISH 128 microinch RMS